Via Praglia, 15 - 10044 Pianezza (TO) - ITALY

Tel. +39-011-9683-111 Fax. +39-011-9683-225



HOW TO ORDER NON-STANDARD-ROLLMAX MICROTUBULAR HEATERS

Diance fill	in a comy of th	sic form and fav it t	- DOTETI	Customor Comis	a at 120 011	0602 225
Please fill	in a cody of tr	nis form and fax it t	OKUIFIL	Customer Servic	:e at +39-u11	-9083-225.

Company	Mr Date			
Telephone Fax	Email			
STRAIGHT HEATER	COILED HEATER			
A B 15 C	Please first choose Cross Selection (with or w/o thermocouple) on the left, as for straight heaters.			
Without Thermocouple – choose the desired Cross Section: ■ 3.3 x 3.3 ■ 2.2 x 4.2 ■ 1.8 x 3.2 ■ 3.7 ■ 3.3 With Thermocouple – choose the desired Cross Section and thermocouple construction: □ J-type Thermocouple ■ 3.3 x 3.3 ■ 3.3 ■ 3.7 ■ 2.2 x 4.2	D ⁴⁵ 20 ⁴² E ⁺¹⁰			
Heated Length A =	Internal Diameter (ID) =			
Unheated Length B =	☐ Tight Spires: Coil Length L =			
Feeding Cable Length C =	☐ Differentiated:			
Cable/Protection Type (see web pics) =	A = B =			
Watt (6,5 A max	No. of Spires in the "C" Length =			
Quantity Required pcs	Unheated Length D =			
	Feeding Cable Length E =			
	Cable/Protection Type (see web pics) =			
	Watt (6,5 A max)			
	Quantity Required pcs Orientation of Feeding Inlet (see web pics):			
	1234			

Note

To avoid delivery of smaller quantities in case of scrap at testing, for each non-standard item some additional units are normally produced, that will be delivered and invoiced. The additional quantity is:

- 1-2 pcs for orders to 40 pcs
- 3-5 pcs for orders of 41-100 pcs
- 5-10 pcs for orders over 100 pcs